

ASTM F1642-04 / GSA TS01 TEST REPORT

Report No.: D8934.02-119-12

Rendered to:

3M COMPANY
St. Paul, Minnesota

PRODUCT TYPE:

Fragment Retention Film on 1" Double Pane Glass with Film Attachment System

SERIES/MODEL:

3M™ Scotchshield™ Ultra S800 Safety and Security Window Film
with
3M™ Impact Protection Profile Film Attachment System
or
3M™ Impact Protection Adhesive Film Attachment System

This report contains in its entirety:

Cover Page: 1 page
Summary of Results: 1 page
Report Body: 16 pages
Test Facility: 1 page
Pressure-Time Plots: 20 pages
Photographs: 25 pages
Drawings: 9 pages

Test Completion Date: 08/27/14
Report Date: 11/13/14
Test Record Retention Date: 08/27/18

Summary of Results

Specimen No.	Film Attachment Type	Average Peak Reflected Pressure	Average Positive Phase Impulse	Average Positive Phase Duration	GSA Performance Condition	ASTM F1642-04 Hazard Rating	ASTM F2912-11 System Rating
1	IPP	8.81 psi	59 psi-msec	14.48 msec	3A	Minimal Hazard	Minimal Hazard (H2)
2		8.79 psi	58 psi-msec	14.66 msec	3A	Minimal Hazard	
3		9.03 psi	60 psi-msec	15.64 msec	2	No Hazard	
4		6.50 psi	40 psi-msec	12.62 msec	3A	Very Low Hazard	N/A
5		9.92 psi	84 psi-msec	-- ¹	5	High Hazard	
6	IPA	9.82 psi	78 psi-msec	16.18 msec	2	No Hazard	No Hazard (H1)
7		9.68 psi	80 psi-msec	19.49 msec	2	No Hazard	
8		10.43 psi	90 psi-msec	17.24 msec	4	Low Hazard	
9		10.74 psi	89 psi-msec	17.48 msec	2	No Hazard	
10		10.36 psi	78 psi-msec	-- ¹	2	Minimal Hazard	N/A

¹ Readings at pressure sensors did not cross zero during the data capture.

Reference must be made to Report No. D8934.02-119-12, dated 11/13/14 for complete test specimen description and detailed test results.

1.0 Report Issued To: 3M Renewable Energy Division
3M Center, Building 235, E-330-3D-02
St. Paul, Minnesota 55144

2.0 Test Laboratory: Architectural Testing, Inc.
130 Derry Court
York, Pennsylvania 17406
717-764-7700

3.0 Project Summary:

3.1 Product Type: Fragment Retention Film on 1" Double Pane Glass with Film Attachment System

3.2 Series/Model: 3MTM ScotchshieldTM Ultra S800 Safety and Security Window Film with 3MTM Impact Protection Profile or 3MTM Impact Protection Adhesive

3.3 Compliance Statement: Results obtained are tested values and were secured by using the designated test methods. This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. It is the exclusive property of the client so named herein and relates only to the specimens tested. This report may not be reproduced, except in full, without the written approval of Architectural Testing, Inc.

3.4 Test Dates: 07/23/2014 - 08/27/2014

3.5 Test Facility: Architectural Testing, Inc.'s shock tube is housed in a 10,000 square foot state-of-the-art test facility located in York, Pennsylvania. Blast loadings are produced on the specimen to simulate the effects of a high explosive charge at a specified standoff distance. Shock waves are generated by the sudden rupturing of a thin aluminum membrane. The shock wave expands as it travels down the tube, and impacts the target with a specific positive pressure and impulse. A photograph of the shock tube is provided in Figure #1 of Appendix A.

3.6 Test Sample Source: The test specimens were provided by the client. Representative samples of the test specimens will be retained by Architectural Testing for a minimum of four years from the test completion date.

3.7 Drawing Reference: The test specimen drawings have been reviewed by Architectural Testing and are representative of the test specimens reported herein. Test specimen construction was verified by Architectural Testing per the drawings located in Appendix D. Any deviations are documented herein or on the drawings.

3.0 Project Summary: (Continued)

3.8 Data Acquisition: In accordance with ASTM F1642-04 and GSA TS01, four reflective pressure transducers are utilized to record data at a 1MHz sample rate. Two reflective pressure transducers are located on the specimen holder at the top and right side (when viewed from the interior). A third pressure transducer is located on the shell to the exterior of the specimen, and a fourth is located in the witness chamber, directly to the interior of the specimen holder. A sketch of the specimen holder and corresponding reflective pressure sensor locations are provided in Figure #2 of Appendix A.

3.9 List of Official Observers:

<u>Name</u>	<u>Company</u>
Josh Scott	Architectural Testing, Inc.
Isaiah W. Gebhart	Architectural Testing, Inc.
Steven A. Neff	Architectural Testing, Inc.
Travis A. Hoover	Architectural Testing, Inc.
Joseph A. Reed, P.E.	Architectural Testing, Inc.
Emily C. Riley	Architectural Testing, Inc.

4.0 Test Specifications:

ASTM F1642-04, *Standard Test Method for Glazing and Glazing Systems Subject to Airblast Loading*

ASTM F2912-11, *Standard Specification for Glazing and Glazing Systems Subject to Airblast Loading*

GSA-TS01-2003, *US General Services Administration Standard Test Method for Glazing and Window Systems Subject to Dynamic Overpressure Loadings*

5.0 Test Specimen Description: The following descriptions apply to all specimens.

5.1 Product Sizes:

Measured Dimensions	Width (inches)	Height (inches)
Overall size	40-1/2	48-1/2
Fixed Day Lite Opening	35-1/4	43-1/4

5.2 Frame Construction:

Frame Member	Material	Description
Head, sill and jambs	Aluminum	Extruded
Pressure plate	Aluminum	Extruded, secured to head sill, and jambs using #1/4 x 1-1/2" long hex head self-tapping screws located 2" from each end and spaced 4" on center
Face cap	Aluminum	Extruded, snaps into place on pressure plate

	Joinery Type	Detail
All corners	Square Cut	Butted and secured using extruded aluminum shear blocks (Reference Drawings ASSY-DOUBLE-39.4x47.3_ULTRA-IPP, Details C and D; and ASSY-DOUBLE-39.4x47.3_ULTRA, Details C and D)
Jambs	N/A	The jambs were secured to each shear block at the head and sill ends using four #1/4 x 1-1/2" long hex head screws
Head/Sill	N/A	The shear blocks utilized a leg that was fitted to a channel in the head and sill. The shear blocks were secured to the head and sill ends using two #10 x 1-1/4" long Phillips pan head screws.

5.0 Test Specimen Description: (Continued)

5.3 Glazing:

Glass Type	Interior Lite	Exterior Lite	Glazing Bite
1" IG	1/4" annealed	1/4" annealed	1/2"

Spacer: Aluminum reinforced butyl

Glazing Method: All specimens utilized an 8 mil micro-layered safety and security film adhered to the interior surface of the glass. The glass was exterior glazed against a kerf-mounted rubber gasket and secured with extruded aluminum pressure plate. The glass was secured in place from the interior using either a 3M™ Impact Protection Profile (IPP), a flexible-mechanical rubber gasket type film attachment (Reference Drawing ASSY-DOUBLE-39.4x47.3_ULTRA-IPP, Details C, D, and E), or a continuous bead of 3M™ Impact Protection Adhesive (IPA) structural sealant (Reference ASSY-DOUBLE-39.4x47.3_ULTRA, Details C, D, and E).

5.4 Hardware: No hardware was utilized.

5.5 Reinforcement: No reinforcement was utilized.

6.0 Installation: The specimens were placed directly into the shock tube test frame.

7.0 Test Results: The results are tabulated as follows:

Test Specimen #1:

Description	Results
Ambient Temperature	85°F
Glazing Temperature	85°F
ASTM Hazard Rating	Minimal Hazard
GSA Performance Condition	3A

Peak Positive Pressure	
Top Pressure	9.19 psi
Right Pressure	9.11 psi
Shell Pressure	8.14 psi
Average Pressure	8.81 psi
Witness Chamber Pressure	0.44 psi

Peak Positive Phase Duration	
Top Duration	16.16 msec
Right Duration	13.95 msec
Shell Duration	13.33 msec
Average Duration	14.48 msec

Peak Positive Phase Impulse	
Top Impulse	59 psi*msec
Right Impulse	60 psi*msec
Shell Impulse	59 psi*msec
Average Impulse	59 psi*msec

Glazing Response	
Exterior Lite	Shattered
Interior Lite	Fractured
Glazing Pullout Length and Location	12-1/2" along head
Glazing Tearing	1" lower left corner

Witness Chamber Results
A dusting of glass was deposited on the witness chamber floor.

Pressure time plots are presented in Appendix B. Pre-test and post-test photographs are provided in Appendix C.

7.0 Test Results: (Continued)

Test Specimen #2:

Description	Results
Ambient Temperature	87°F
Glazing Temperature	88°F
ASTM Hazard Rating	Minimal Hazard
GSA Performance Condition	3A

Peak Positive Pressure	
Top Pressure	9.00 psi
Right Pressure	9.20 psi
Shell Pressure	8.17 psi
Average Pressure	8.79 psi
Witness Chamber Pressure	0.36 psi

Peak Positive Phase Duration	
Top Duration	14.98 msec
Right Duration	14.60 msec
Shell Duration	14.40 msec
Average Duration	14.66 msec

Peak Positive Phase Impulse	
Top Impulse	58 psi*msec
Right Impulse	58 psi*msec
Shell Impulse	58 psi*msec
Average Impulse	58 psi*msec

Glazing Response	
Exterior Lite	Shattered
Interior Lite	Fractured
Glazing Pullout Length and Location	6" at lower left
Glazing Tearing	None

Witness Chamber Results
No debris was observed.

Pressure time plots are presented in Appendix B. Pre-test and post-test photographs are provided in Appendix C.

7.0 Test Results: (Continued)

Test Specimen #3:

Description	Results
Ambient Temperature	80°F
Glazing Temperature	79°F
ASTM Hazard Rating	No Hazard
GSA Performance Condition	2

Peak Positive Pressure	
Top Pressure	9.41 psi
Right Pressure	9.31 psi
Shell Pressure	8.36 psi
Average Pressure	9.03 psi
Witness Chamber Pressure	1.02 psi

Peak Positive Phase Duration	
Top Duration	14.97 msec
Right Duration	16.83 msec
Shell Duration	15.13 msec
Average Duration	15.64 msec

Peak Positive Phase Impulse	
Top Impulse	61 psi*msec
Right Impulse	60 psi*msec
Shell Impulse	60 psi*msec
Average Impulse	60 psi*msec

Glazing Response	
Exterior Lite	Shattered
Interior Lite	Fractured
Glazing Pullout Length and Location	None
Glazing Tearing	None

Witness Chamber Results
No debris was observed.

Pressure time plots are presented in Appendix B. Pre-test and post-test photographs are provided in Appendix C.

7.0 Test Results: (Continued)

Test Specimen #4:

Description	Results
Ambient Temperature	81°F
Glazing Temperature	81°F
ASTM Hazard Rating	Very Low Hazard
GSA Performance Condition	3A

Peak Positive Pressure	
Top Pressure	6.46 psi
Right Pressure	6.98 psi
Shell Pressure	6.07 psi
Average Pressure	6.50 psi
Witness Chamber Pressure	0.36 psi

Peak Positive Phase Duration	
Top Duration	12.28 msec
Right Duration	13.69 msec
Shell Duration	12.88 msec
Average Duration	12.62 msec

Peak Positive Phase Impulse	
Top Impulse	40 psi*msec
Right Impulse	40 psi*msec
Shell Impulse	40 psi*msec
Average Impulse	40 psi*msec

Glazing Response	
Exterior Lite	Shattered
Interior Lite	Fractured
Glazing Pullout Length and Location	24-1/2" along sill and 15" along head
Glazing Tearing	None

Witness Chamber Results
No debris was observed.

Pressure time plots are presented in Appendix B. Pre-test and post-test photographs are provided in Appendix C.

7.0 Test Results: (Continued)

Test Specimen #5:

Description	Results
Ambient Temperature	89°F
Glazing Temperature	92°F
ASTM Hazard Rating	High Hazard
GSA Performance Condition	5

Peak Positive Pressure	
Top Pressure	10.01 psi
Right Pressure	10.12 psi
Shell Pressure	9.63 psi
Average Pressure	9.92 psi
Witness Chamber Pressure	0.66 psi

Peak Positive Phase Duration	
Top Duration	-- ¹
Right Duration	-- ¹
Shell Duration	-- ¹
Average Duration	-- ¹

¹ Readings at pressure sensors did not cross zero during the data capture.

Peak Positive Phase Impulse	
Top Impulse	84 psi*msec
Right Impulse	85 psi*msec
Shell Impulse	84 psi*msec
Average Impulse	84 psi*msec

Glazing Response	
Exterior Lite	Shattered
Interior Lite	Fractured and blown out
Glazing Pullout Length and Location	Entire interior lite deglazed
Glazing Tearing	N/A

Witness Chamber Results
The interior lite landed on the witness chamber floor at the panel. Glazing lite impacted panel and penetrated into the second layer of the witness panel.

Pressure time plots are presented in Appendix B. Pre-test and post-test photographs are provided in Appendix C.

7.0 Test Results: (Continued)

Test Specimen #6:

Description	Results
Ambient Temperature	81°F
Glazing Temperature	80°F
ASTM Hazard Rating	No Hazard
GSA Performance Condition	2

Peak Positive Pressure	
Top Pressure	10.21 psi
Right Pressure	10.28 psi
Shell Pressure	8.97 psi
Average Pressure	9.82 psi
Witness Chamber Pressure	0.45 psi

Peak Positive Phase Duration	
Top Duration	-- ¹
Right Duration	16.33 msec
Shell Duration	16.07 msec
Average Duration	16.18 msec

¹ Readings at pressure sensors did not cross zero during the data capture.

Peak Positive Phase Impulse	
Top Impulse	78 psi*msec
Right Impulse	78 psi*msec
Shell Impulse	78 psi*msec
Average Impulse	78 psi*msec

Glazing Response	
Exterior Lite	Shattered
Interior Lite	Fractured
Glazing Pullout Length and Location	None
Glazing Tearing	None

Witness Chamber Results
No debris was observed.

Pressure time plots are presented in Appendix B. Pre-test and post-test photographs are provided in Appendix C.

7.0 Test Results: (Continued)

Test Specimen #7:

Description	Results
Ambient Temperature	84°F
Glazing Temperature	83°F
ASTM Hazard Rating	No Hazard
GSA Performance Condition	2

Peak Positive Pressure	
Top Pressure	10.01 psi
Right Pressure	10.18 psi
Shell Pressure	8.84 psi
Average Pressure	9.68 psi
Witness Chamber Pressure	0.43 psi

Peak Positive Phase Duration	
Top Duration	-- ¹
Right Duration	19.68 msec
Shell Duration	19.30 msec
Average Duration	19.49 msec

¹ Readings at pressure sensors did not cross zero during the data capture.

Peak Positive Phase Impulse	
Top Impulse	82 psi*msec
Right Impulse	79 psi*msec
Shell Impulse	79 psi*msec
Average Impulse	80 psi*msec

Glazing Response	
Exterior Lite	Shattered
Interior Lite	Fractured
Glazing Pullout Length and Location	None
Glazing Tearing	None

Witness Chamber Results
A dusting of glass was deposited on the witness chamber floor.

Pressure time plots are presented in Appendix B. Pre-test and post-test photographs are provided in Appendix C.

7.0 Test Results: (Continued)

Test Specimen #8:

Description	Results
Ambient Temperature	86°F
Glazing Temperature	87°F
ASTM Hazard Rating	Low Hazard
GSA Performance Condition	4

Peak Positive Pressure	
Top Pressure	10.79 psi
Right Pressure	10.48 psi
Shell Pressure	10.01 psi
Average Pressure	10.43 psi
Witness Chamber Pressure	0.66 psi

Peak Positive Phase Duration	
Top Duration	19.11 msec
Right Duration	16.41 msec
Shell Duration	16.21 msec
Average Duration	17.24 msec

Peak Positive Phase Impulse	
Top Impulse	90 psi*msec
Right Impulse	90 psi*msec
Shell Impulse	90 psi*msec
Average Impulse	90 psi*msec

Glazing Response	
Exterior Lite	Shattered
Interior Lite	Fractured
Glazing Pullout Length and Location	None
Glazing Tearing	6" at upper right corner

Witness Chamber Results
Sum total united dimension of fragments on witness panel floor between 1m and 3m from the specimen was >10".

Pressure time plots are presented in Appendix B. Pre-test and post-test photographs are provided in Appendix C.

7.0 Test Results: (Continued)

Test Specimen #9:

Description	Results
Ambient Temperature	87°F
Glazing Temperature	88°F
ASTM Hazard Rating	No Hazard
GSA Performance Condition	2

Peak Positive Pressure	
Top Pressure	10.95 psi
Right Pressure	11.08 psi
Shell Pressure	10.18 psi
Average Pressure	10.74 psi
Witness Chamber Pressure	0.74 psi

Peak Positive Phase Duration	
Top Duration	16.42 msec
Right Duration	18.54 msec
Shell Duration	-- ¹
Average Duration	17.48 msec

¹ Readings at pressure sensors did not cross zero during the data capture.

Peak Positive Phase Impulse	
Top Impulse	89 psi*msec
Right Impulse	89 psi*msec
Shell Impulse	89 psi*msec
Average Impulse	89 psi*msec

Glazing Response	
Exterior Lite	Shattered
Interior Lite	Fractured
Glazing Pullout Length and Location	None
Glazing Tearing	None

Witness Chamber Results
No debris was observed.

Pressure time plots are presented in Appendix B. Pre-test and post-test photographs are provided in Appendix C.

7.0 Test Results: (Continued)

Test Specimen #10:

Description	Results
Ambient Temperature	89°F
Glazing Temperature	90°F
ASTM Hazard Rating	Minimal Hazard
GSA Performance Condition	2

Peak Positive Pressure	
Top Pressure	10.57 psi
Right Pressure	10.64 psi
Shell Pressure	9.86 psi
Average Pressure	10.36 psi
Witness Chamber Pressure	0.42 psi

Peak Positive Phase Duration	
Top Duration	-- ^I
Right Duration	-- ^I
Shell Duration	-- ^I
Average Duration	-- ^I

^I Readings at pressure sensors did not cross zero during the data capture.

Peak Positive Phase Impulse	
Top Impulse	78 psi*msec
Right Impulse	78 psi*msec
Shell Impulse	78 psi*msec
Average Impulse	78 psi*msec

Glazing Response	
Exterior Lite	Shattered
Interior Lite	Fractured
Glazing Pullout Length and Location	None
Glazing Tearing	3/4" long and 1" long

Witness Chamber Results
No debris was observed.

Pressure time plots are presented in Appendix B. Pre-test and post-test photographs are provided in Appendix C.

8.0 Closing Statement

Architectural Testing will service this report for the entire test record retention period. Test records that are retained such as detailed drawings, datasheets, representative samples of test specimens, or other pertinent project documentation will be retained by Architectural Testing, Inc. for the entire test record retention period.

Results obtained are tested values and were secured using the designated test methods. This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. It is the exclusive property of the client so named herein and relates only to the specimens tested. This report may not be reproduced, except in full, without the written approval of Architectural Testing, Inc.

For ARCHITECTURAL TESTING, INC.:

Emily C. Riley - Project Manager
Structural Systems Testing

Joseph A. Reed, P.E. - Director
Engineering

ECR/jar:jas

Attachments (pages): This report is complete only when all attachments listed are included.

- Appendix A - Test Facility (1)
- Appendix B - Pressure Time Plots (20)
- Appendix C - Photographs (25)
- Appendix D - Drawings (9)

Revision Log

<u>Rev. #</u>	<u>Date</u>	<u>Page(s)</u>	<u>Revision(s)</u>
0	11/13/14	N/A	Original report issue



Report No.: D8934.02-119-12
Report Date: 11/13/14
Test Record Retention Date: 08/27/18

APPENDIX A

Test Facility



Figure #1
Shock Tube and Test Facility




Figure #2
Pressure Sensor Locations




Report No.: D8934.02-119-12
Report Date: 11/13/14
Test Record Retention Date: 08/27/18

APPENDIX B


Pressure Time Plots

Specimen #1



Peak Pressure: 8.42 psi at 5.60 ms
 Duration: 16.63 ms


Test Date: 7/25/2014
 Test Time: 9:05 am



Peak Pressure: 9.50 psi at 5.30 ms
 Duration: 17.34 ms


Test Date: 7/25/2014
 Test Time: 9:05 am

Specimen #1: (Continued)



Peak Pressure: 9.61 psi at 5.30 ms
 Duration: 13.24 ms


Test Date: 7/25/2014
 Test Time: 9:05 am



Peak Pressure: 0.49 psi at 23.72 ms
 Duration: 1.35 ms


Test Date: 7/25/2014
 Test Time: 9:05 am

Specimen #2



Peak Pressure: 8.21 psi at 6.77 ms
 Duration: 15.32 ms


Test Date: 8/4/2014
 Test Time: 2:58 pm



Peak Pressure: 8.80 psi at 5.32 ms
 Duration: 16.56 ms


Test Date: 8/4/2014
 Test Time: 2:58 pm

Specimen #2: (Continued)



Peak Pressure: 8.64 psi at 5.31 ms
 Duration: 14.08 ms


Test Date: 8/4/2014
 Test Time: 2:58 pm



Peak Pressure: 0.48 psi at 27.09 ms
 Duration: 0.00 ms


Test Date: 8/4/2014
 Test Time: 2:58 pm

Specimen #3



Peak Pressure: 8.25 psi at 5.60 ms
 Duration: 15.67 ms


Test Date: 8/4/2014
 Test Time: 11:57 am



Peak Pressure: 9.29 psi at 5.30 ms
 Duration: 16.24 ms


Test Date: 8/4/2014
 Test Time: 11:57 am

Specimen #3: (Continued)



Peak Pressure: 9.15 psi at 5.31 ms
 Duration: 15.21 ms


Test Date: 8/4/2014
 Test Time: 11:57 am



Peak Pressure: 0.49 psi at 23.65 ms
 Duration: 4.06 ms


Test Date: 8/4/2014
 Test Time: 11:57 am

Specimen #4



Peak Pressure: 6.37 psi at 6.43 ms
 Duration: 12.35 ms


Test Date: 7/24/2014
 Test Time: 2:32 pm



Peak Pressure: 7.38 psi at 5.50 ms
 Duration: 13.28 ms


Test Date: 7/24/2014
 Test Time: 2:32 pm

Specimen #4: (Continued)



Peak Pressure: 7.10 psi at 5.43 ms
 Duration: 12.41 ms


Test Date: 7/24/2014
 Test Time: 2:32 pm



Peak Pressure: 0.35 psi at 10.64 ms
 Duration: 4.02 ms


Test Date: 7/24/2014
 Test Time: 2:32 pm

Specimen #5



Peak Pressure: 8.97 psi at 6.33 ms
 Duration: 16.60 ms


Test Date: 8/6/2014
 Test Time: 10:15 am



Peak Pressure: 10.00 psi at 5.29 ms
 Duration: 19.27 ms


Test Date: 8/6/2014
 Test Time: 10:15 am

Specimen #5: (Continued)



Peak Pressure: 9.88 psi at 5.31 ms
 Duration: 16.21 ms


Test Date: 8/6/2014
 Test Time: 10:15 am



Peak Pressure: 0.78 psi at 18.35 ms
 Duration: 2.49 ms


Test Date: 8/6/2014
 Test Time: 10:15 am

Specimen #6



Peak Pressure: 8.62 psi at 5.60 ms
 Duration: 17.66 ms


Test Date: 8/27/2014
 Test Time: 2:43 pm



Peak Pressure: 9.53 psi at 5.31 ms
 Duration: 16.14 ms


Test Date: 8/27/2014
 Test Time: 2:43 pm

Specimen #6: (Continued)



Peak Pressure: 9.68 psi at 5.30 ms
 Duration: 15.82 ms


Test Date: 8/27/2014
 Test Time: 2:43 pm



Peak Pressure: 0.64 psi at 26.77 ms
 Duration: 0.00 ms


Test Date: 8/27/2014
 Test Time: 2:43 pm

Specimen #7



Peak Pressure: 9.86 psi at 6.64 ms
 Duration: 0.00 ms


Test Date: 8/27/2014
 Test Time: 4:17 pm



Peak Pressure: 10.64 psi at 5.32 ms
 Duration: 0.00 ms


Test Date: 8/27/2014
 Test Time: 4:17 pm

Specimen #7: (Continued)



Peak Pressure: 10.57 psi at 5.30 ms
 Duration: 0.00 ms


Test Date: 8/27/2014
 Test Time: 4:17 pm



Peak Pressure: 0.42 psi at 10.57 ms
 Duration: 9.24 ms


Test Date: 8/27/2014
 Test Time: 4:17 pm

Specimen #8



Peak Pressure: 8.94 psi at 6.73 ms
 Duration: 15.20 ms


Test Date: 8/28/2014
 Test Time: 2:59 pm



Peak Pressure: 9.64 psi at 5.29 ms
 Duration: 16.72 ms


Test Date: 8/28/2014
 Test Time: 2:59 pm

Specimen #8: (Continued)



Peak Pressure: 9.80 psi at 5.32 ms
 Duration: 0.00 ms


Test Date: 8/28/2014
 Test Time: 2:59 pm



Peak Pressure: 0.39 psi at 22.76 ms
 Duration: 0.00 ms


Test Date: 8/28/2014
 Test Time: 2:59 pm

Specimen #9



Peak Pressure: 9.94 psi at 6.45 ms
 Duration: 0.00 ms


Test Date: 8/26/2014
 Test Time: 12:09 pm



Peak Pressure: 10.78 psi at 5.31 ms
 Duration: 16.56 ms


Test Date: 8/26/2014
 Test Time: 12:09 pm

Specimen #9: (Continued)



Peak Pressure: 10.85 psi at 5.30 ms
 Duration: 19.83 ms


Test Date: 8/26/2014
 Test Time: 12:09 pm



Peak Pressure: 10.85 psi at 5.30 ms
 Duration: 19.83 ms


Test Date: 8/26/2014
 Test Time: 12:09 pm

Specimen #10



Peak Pressure: 8.64 psi at 5.67 ms
 Duration: 17.31 ms


Test Date: 8/29/2014
 Test Time: 9:16 am



Peak Pressure: 9.76 psi at 5.41 ms
 Duration: 17.19 ms


Test Date: 8/29/2014
 Test Time: 9:16 am

Specimen #10: (Continued)



Peak Pressure: 9.79 psi at 5.44 ms
 Duration: 18.46 ms

Test Date: 8/29/2014
 Test Time: 9:16 am



Peak Pressure: 0.37 psi at 10.69 ms
 Duration: 6.01 ms

Test Date: 8/29/2014
 Test Time: 9:16 am



Report No.: D8934.02-119-12
Report Date: 11/13/14
Test Record Retention Date: 08/27/18

APPENDIX C

Photographs



Photo No. 1
Pre-test Specimen #1, Interior



Photo No. 2
Post-test Specimen #1, Interior



Photo No. 3
Post-test Specimen #1, Witness Chamber



Photo No. 4
Pre-test Specimen #2, Interior



Photo No. 5
Post-test Specimen #2, Interior




Photo No. 6
Post-test Specimen #2, Witness Chamber



Photo No. 7
Pre-test Specimen #3, Interior



Photo No. 8
Post-test Specimen #3, Interior




Photo No. 9
Post-test Specimen #3, Witness Chamber



Photo No. 10
Pre-test Specimen #4, Interior



Photo No. 11
Post-test Specimen #4, Interior



Photo No. 12
Post-test Specimen #4, Witness Chamber



Photo No. 13
Pre-test Specimen #5, Interior



Photo No. 14
Post-test Specimen #5, Interior




Photo No. 15
Post-test Specimen #5, Witness Chamber



Photo No. 16
Pre-test Specimen #6, Interior



Photo No. 17
Post-test Specimen #6, Interior



Photo No. 18
Post-test Specimen #6, Witness Chamber



Photo No. 19
Pre-test Specimen #7, Interior



Photo No. 20
Post-test Specimen #7, Interior



Photo No. 21
Post-test Specimen #7, Witness Chamber



Photo No. 22
Pre-test Specimen #8, Interior




Photo No. 23
Post-test Specimen #8, Interior




Photo No. 24
Post-test Specimen #8, Witness Chamber



Photo No. 25
Pre-test Specimen #9, Interior




Photo No. 26
Post-test Specimen #9, Interior



Photo No. 27
Post-test Specimen #9, Witness Chamber



Photo No. 28
Pre-test Specimen #10, Interior



Photo No. 29
Post-test Specimen #10, Interior





Photo No. 30
Post-test Specimen #10, Witness Chamber



Report No.: D8934.02-119-12
Report Date: 11/13/14
Test Record Retention Date: 08/27/18

APPENDIX D

Drawings



Architectural Testing

Test sample complies with these details.
Deviations are noted.


Report # **D8934**

Date **11/12/14** Tech **ER**

DESIGN REFERENCE	TEST ASSUMPTIONS	TEST DATE AND LOCATION	TEST TIME
1	1	SEP 16, 2014	1
2	2	SEP 16, 2014	2
3	3	SEP 16, 2014	3
4	4	SEP 16, 2014	4
5	5	SEP 16, 2014	5
6	6	SEP 16, 2014	6
7	7	SEP 16, 2014	7
8	8	SEP 16, 2014	8
9	9	SEP 16, 2014	9
10	10	SEP 16, 2014	10
11	11	SEP 16, 2014	11
12	12	SEP 16, 2014	12
13	13	SEP 16, 2014	13
14	14	SEP 16, 2014	14
15	15	SEP 16, 2014	15
16	16	SEP 16, 2014	16
17	17	SEP 16, 2014	17
18	18	SEP 16, 2014	18
19	19	SEP 16, 2014	19
20	20	SEP 16, 2014	20
21	21	SEP 16, 2014	21
22	22	SEP 16, 2014	22
23	23	SEP 16, 2014	23
24	24	SEP 16, 2014	24
25	25	SEP 16, 2014	25
26	26	SEP 16, 2014	26
27	27	SEP 16, 2014	27
28	28	SEP 16, 2014	28
29	29	SEP 16, 2014	29
30	30	SEP 16, 2014	30
31	31	SEP 16, 2014	31
32	32	SEP 16, 2014	32
33	33	SEP 16, 2014	33
34	34	SEP 16, 2014	34
35	35	SEP 16, 2014	35
36	36	SEP 16, 2014	36
37	37	SEP 16, 2014	37
38	38	SEP 16, 2014	38
39	39	SEP 16, 2014	39
40	40	SEP 16, 2014	40
41	41	SEP 16, 2014	41
42	42	SEP 16, 2014	42
43	43	SEP 16, 2014	43
44	44	SEP 16, 2014	44
45	45	SEP 16, 2014	45
46	46	SEP 16, 2014	46
47	47	SEP 16, 2014	47
48	48	SEP 16, 2014	48
49	49	SEP 16, 2014	49
50	50	SEP 16, 2014	50
51	51	SEP 16, 2014	51
52	52	SEP 16, 2014	52
53	53	SEP 16, 2014	53
54	54	SEP 16, 2014	54
55	55	SEP 16, 2014	55
56	56	SEP 16, 2014	56
57	57	SEP 16, 2014	57
58	58	SEP 16, 2014	58
59	59	SEP 16, 2014	59
60	60	SEP 16, 2014	60
61	61	SEP 16, 2014	61
62	62	SEP 16, 2014	62
63	63	SEP 16, 2014	63
64	64	SEP 16, 2014	64
65	65	SEP 16, 2014	65
66	66	SEP 16, 2014	66
67	67	SEP 16, 2014	67
68	68	SEP 16, 2014	68
69	69	SEP 16, 2014	69
70	70	SEP 16, 2014	70
71	71	SEP 16, 2014	71
72	72	SEP 16, 2014	72
73	73	SEP 16, 2014	73
74	74	SEP 16, 2014	74
75	75	SEP 16, 2014	75
76	76	SEP 16, 2014	76
77	77	SEP 16, 2014	77
78	78	SEP 16, 2014	78
79	79	SEP 16, 2014	79
80	80	SEP 16, 2014	80
81	81	SEP 16, 2014	81
82	82	SEP 16, 2014	82
83	83	SEP 16, 2014	83
84	84	SEP 16, 2014	84
85	85	SEP 16, 2014	85
86	86	SEP 16, 2014	86
87	87	SEP 16, 2014	87
88	88	SEP 16, 2014	88
89	89	SEP 16, 2014	89
90	90	SEP 16, 2014	90
91	91	SEP 16, 2014	91
92	92	SEP 16, 2014	92
93	93	SEP 16, 2014	93
94	94	SEP 16, 2014	94
95	95	SEP 16, 2014	95
96	96	SEP 16, 2014	96
97	97	SEP 16, 2014	97
98	98	SEP 16, 2014	98
99	99	SEP 16, 2014	99
100	100	SEP 16, 2014	100




SECTION B - B




Test sample complies with these details.
Deviations are noted.

Date 11/12/14 Tech COE

[illegible]



SECTION A - A



SECTION B - B





Test sample complies with these details.
Deviations are noted.

Report # **D8934**

Date **11/12/14** Tech **CR**

SECTION	DATE	DESCRIPTION	DATE	UNIT
1	12/18/2014	12/18/2014		
2	12/18/2014	12/18/2014		
3	12/18/2014	12/18/2014		
4	12/18/2014	12/18/2014		
5	12/18/2014	12/18/2014		
6	12/18/2014	12/18/2014		
7	12/18/2014	12/18/2014		
8	12/18/2014	12/18/2014		
9	12/18/2014	12/18/2014		
10	12/18/2014	12/18/2014		
11	12/18/2014	12/18/2014		
12	12/18/2014	12/18/2014		
13	12/18/2014	12/18/2014		
14	12/18/2014	12/18/2014		
15	12/18/2014	12/18/2014		
16	12/18/2014	12/18/2014		
17	12/18/2014	12/18/2014		
18	12/18/2014	12/18/2014		
19	12/18/2014	12/18/2014		
20	12/18/2014	12/18/2014		
21	12/18/2014	12/18/2014		
22	12/18/2014	12/18/2014		
23	12/18/2014	12/18/2014		
24	12/18/2014	12/18/2014		
25	12/18/2014	12/18/2014		
26	12/18/2014	12/18/2014		
27	12/18/2014	12/18/2014		
28	12/18/2014	12/18/2014		
29	12/18/2014	12/18/2014		
30	12/18/2014	12/18/2014		
31	12/18/2014	12/18/2014		
32	12/18/2014	12/18/2014		
33	12/18/2014	12/18/2014		
34	12/18/2014	12/18/2014		
35	12/18/2014	12/18/2014		
36	12/18/2014	12/18/2014		
37	12/18/2014	12/18/2014		
38	12/18/2014	12/18/2014		
39	12/18/2014	12/18/2014		
40	12/18/2014	12/18/2014		
41	12/18/2014	12/18/2014		
42	12/18/2014	12/18/2014		
43	12/18/2014	12/18/2014		
44	12/18/2014	12/18/2014		
45	12/18/2014	12/18/2014		
46	12/18/2014	12/18/2014		
47	12/18/2014	12/18/2014		
48	12/18/2014	12/18/2014		
49	12/18/2014	12/18/2014		
50	12/18/2014	12/18/2014		
51	12/18/2014	12/18/2014		
52	12/18/2014	12/18/2014		
53	12/18/2014	12/18/2014		
54	12/18/2014	12/18/2014		
55	12/18/2014	12/18/2014		
56	12/18/2014	12/18/2014		
57	12/18/2014	12/18/2014		
58	12/18/2014	12/18/2014		
59	12/18/2014	12/18/2014		
60	12/18/2014	12/18/2014		
61	12/18/2014	12/18/2014		
62	12/18/2014	12/18/2014		
63	12/18/2014	12/18/2014		
64	12/18/2014	12/18/2014		
65	12/18/2014	12/18/2014		
66	12/18/2014	12/18/2014		
67	12/18/2014	12/18/2014		
68	12/18/2014	12/18/2014		
69	12/18/2014	12/18/2014		
70	12/18/2014	12/18/2014		
71	12/18/2014	12/18/2014		
72	12/18/2014	12/18/2014		
73	12/18/2014	12/18/2014		
74	12/18/2014	12/18/2014		
75	12/18/2014	12/18/2014		
76	12/18/2014	12/18/2014		
77	12/18/2014	12/18/2014		
78	12/18/2014	12/18/2014		
79	12/18/2014	12/18/2014		
80	12/18/2014	12/18/2014		
81	12/18/2014	12/18/2014		
82	12/18/2014	12/18/2014		
83	12/18/2014	12/18/2014		
84	12/18/2014	12/18/2014		
85	12/18/2014	12/18/2014		
86	12/18/2014	12/18/2014		
87	12/18/2014	12/18/2014		
88	12/18/2014	12/18/2014		
89	12/18/2014	12/18/2014		
90	12/18/2014	12/18/2014		
91	12/18/2014	12/18/2014		
92	12/18/2014	12/18/2014		
93	12/18/2014	12/18/2014		
94	12/18/2014	12/18/2014		
95	12/18/2014	12/18/2014		
96	12/18/2014	12/18/2014		
97	12/18/2014	12/18/2014		
98	12/18/2014	12/18/2014		
99	12/18/2014	12/18/2014		
100	12/18/2014	12/18/2014		



NOTES:

1. REFERENCE DRAWING ONLY.
2. PART NUMBER: WW-401.
3. PART SUPPLIER: OLD CASTLE BUILDING ENVELOPE.
WWW.OLDCASTLE.COM.



Architectural Testing

Test sample complies with these details.
Deviations are noted.

Report # D8934


Date 11/12/14 Tech SQL

[illegible]



Report # D8934 Tech CR

[illegible]



1. REFERENCE DRAWING ONLY.
2. PART NUMBER: WW-181-01.
3. PART SUPPLIER: OLD CASTLE BUILDING ENVELOPE.
WWW.OLDCASTLE.COM.


Architectural Testing

Test sample complies with these details.
Deviations are noted.

Report # D6934-01

Date 11/12/14 Tech CR

DESIGN REFERENCE		NEXT ASSEMBLY		DIVISION CODE		DO NOT SCALE DRAWING		SCALE 1		TOLERANCES UNLESS NOTED		INCHES .0 ±.02 .000 ±.005 .0000 ±		THIRD ANGLE PROJECTION		INTERPRET PER ASME Y14.5 - 2009		MAX SURFACE ROUGHNESS 10 ✓		ALL SURFACES □ ✓ MARKED ONLY		ANGLES ±0.1°	
ACCESSORIES																							
REV		ECO		ISSUE DATE AND DESCRIPTION		DATE		DATE		DATE		DATE		DATE		DATE		DATE		DATE		DATE	
L.SCHLEIF																							
CHD																							
3M Center		3M Center		3M Center		3M Center		3M Center		3M Center		3M Center		3M Center		3M Center		3M Center		3M Center		3M Center	
SR. PROJ.		SR. PROJ.		SR. PROJ.		SR. PROJ.		SR. PROJ.		SR. PROJ.		SR. PROJ.		SR. PROJ.		SR. PROJ.		SR. PROJ.		SR. PROJ.		SR. PROJ.	
MW 55144		MW 55144		MW 55144		MW 55144		MW 55144		MW 55144		MW 55144		MW 55144		MW 55144		MW 55144		MW 55144		MW 55144	
TITLE		SHR BLK JAM & MULLS-WW-181-01		SHR BLK JAM & MULLS-WW-181-01		SHR BLK JAM & MULLS-WW-181-01		SHR BLK JAM & MULLS-WW-181-01		SHR BLK JAM & MULLS-WW-181-01		SHR BLK JAM & MULLS-WW-181-01		SHR BLK JAM & MULLS-WW-181-01		SHR BLK JAM & MULLS-WW-181-01		SHR BLK JAM & MULLS-WW-181-01		SHR BLK JAM & MULLS-WW-181-01		SHR BLK JAM & MULLS-WW-181-01	
CAGE NUMBER		SIZE		DRAWING NO.		REV.		REV.		REV.		REV.		REV.		REV.		REV.		REV.		REV.	
B		B		B		B		B		B		B		B		B		B		B		B	
MODEL		DET		LISTS		YES		NO		SHT		1		OF		1		OF		1		OF	



NOTES:

1. REFERENCE DRAWING ONLY.
2. PART NUMBER: WW-110.
3. PART SUPPLIER: OLD CASTLE BUILDING ENVELOPE.
WWW.OLDCASTLE.COM.

DESIGN REFERENCE		NEXT ASSEMBLY		<div> <div>1</div> <div>OCT 16, 2014</div> </div>	
<div> <div>REV</div> <div>ECO</div> </div>	<div> <div>DATE</div> <div>OCT 16, 2014</div> </div>		<div> <div>ISSUE DATE AND DESCRIPTION</div> </div>		<div> <div>DRFT</div> <div>CHKD</div> </div>
<div> <div>DRFT</div> <div>L. SCHLEIF</div> </div>		<div> <div>WFO</div> </div>		<div> <div>DATE</div> </div>	
<div> <div>CHKD</div> </div>		<div> <div>DATE</div> </div>		<div> <div>APPL</div> </div>	
<div> <div>DIVISION</div> </div>		<div> <div>DIVISION CODE</div> </div>		<div> <div>© 3M COPYRIGHT 2014</div> </div>	
<div> <div>DO NOT SCALE DRAWING</div> </div>		<div> <div>SCALE</div> <div>1/2</div> </div>		<div> <div>3M Center</div> <div>St. Paul,</div> <div>MIN 55144</div> </div>	
<div> <div>TOLERANCES EXCEPT AS NOTED</div> </div>		<div> <div>INCHES</div> <div>.00 ±</div> <div>.02 ±</div> <div>.000 ±</div> <div>.005 ±</div> <div>.0000 ±</div> </div>		<div> <div>This document and the information it contains are the property of 3M and may not be reproduced or further distributed without the express written permission of 3M. All rights reserved.</div> </div>	
<div> <div>INTERPRET PER ASME Y14.5 - 2009</div> </div>		<div> <div>THIRD ANGLE PROJECTION</div> </div>		<div> <div>FACE CAP WW-110</div> </div>	
<div> <div>MAX SURFACE ROUGHNESS</div> <div>10</div> </div>		<div> <div>ALL SURFACES</div> <div>✓</div> </div>		<div> <div>CAGE NUMBER</div> <div>B</div> </div>	
<div> <div>MARKED ONLY</div> </div>		<div> <div>ANGLES ±0.1°</div> </div>		<div> <div>DRAWING NO.</div> </div>	
<div> <div>REV.</div> <div>1</div> </div>		<div> <div>DEF. LISTS</div> <div>YES</div> <div>NO</div> </div>		<div> <div>SHT 1 OF 1</div> </div>	